




LED Pool/Underwater Recessed lights





X04

- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/RGBW/DMX512
- ◆ Material: Stainless steel cover+body,Tempered glass(Clear/Frosted)
- ◆ Input Voltage: 12V/24V



超薄款灯体可选

Technical Parameter

Model	Size(mm)			Rated Power	Hole Size(mm)	N.W(kg)	Packing Size	Angle (Lens)
	Φ	ΦA	H					
X07	230	65	76	18W	Φ210*H85	2.4kg	52*30*46cm/8pcs	15° /30° /45° /60°
X01	210	52	90	12W	Φ190*H90	1.9kg	47*45.5*34.5cm/8pcs	15° /30° /45° /60°
X06	210	52	80	9W/12W	Φ180*H90	1.8kg	47*47*35cm/8pcs	15° /30° /45° /60°
X02	180	41	85	9W/12W	Φ165*H90	1.5kg	57*38*30cm/12pcs	15° /30° /45° /60°
X03	168	34	80	6W/9W	Φ155*H80	1.3kg	57*38*30cm/12pcs	15° /30° /45° /60°
X04	150	26	85	6W	Φ130*H80	1.05kg	48*31.5*30cm/18pcs	15° /30° /45° /60°
X05	130	26	55	5W	Φ118*H65	1kg	61*45*24cm/24pcs	15° /30° /45° /60°





LED Pool/Underwater Recessed lights



- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/R/G/B
- ◆ Material: Stainless steel cover+body, Tempered glass(Clear/Frosted)
- ◆ Input Voltage: 12V/24V

Technical Parameter

Model	190A	145A
Size	Φ190*H180mm	Φ145*H170mm
Rated Power	12W	6W/7W/9W
Input Voltage	12V/24V	
N.W/G.W	1.6kg	1.15kg
Packing Size	43*42*49cm/12pcs	48*47*35cm/18pcs
Angle(Lens)	15° /30° /45° /60°	15° /30° /45° /60°


Technical Parameter

Model	145	115
Size	Φ145*H170mm	Φ115*H150mm
Rated Power	6W/7W/9W	3W/5W
Input Voltage	12V/24V	
N.W/G.W	0.9kg	0.9kg
Packing Size	48*47*35cm/18pcs	49.5*49.5*29.5cm/32pcs
Angle(Lens)	15° /30° /45° /60°	15° /30° /45° /60°



Technical Parameter

Model	85A	82
Size	Φ85*H125mm	Φ82*H155mm
Rated Power	3W	3W
Input Voltage	12V/24V	
N.W/G.W	0.5kg	0.6kg
Packing Size	56*34*28cm/30pcs	52*52*28cm/50pcs
Angle(Lens)	15° /30° /45° /60°	15° /30° /45° /60°




76

Technical Parameter

Model	Size(mm)		Rated Power	N.W(kg)	Angle (Lens)
	Φ	H			
76	76	106	3W	0.65kg	15° /30° /45° /60°

- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/R/G/B
- ◆ Material: Stainless steel cover+body,Tempered glass (Clear/Frosted)
- ◆ Input Voltage: 12V/24V



G-125

Technical Parameter


Model	Size(mm)			Rated Power	N.W(kg)	Angle (Lens)
	Φ	Φ A	H			
103	105	65	150	3W	0.7kg	15° /30° /45° /60°
125	125	75	185	6W	0.95kg	15° /30° /45° /60°
140	145	85	200	9W	1.25kg	15° /30° /45° /60°



LED Pool/Underwater Recessed lights



Q150




- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/R/G/B
- ◆ Material: Stainless steel cover+body, Tempered glass(Clear/Frosted), ABS box
- ◆ Input Voltage: 12V/24V

Technical Parameter

Model	Size(mm)		Rated Power	Hole Size(mm)	N.W(kg)	Packing Size	Angle (Lens)
	Φ	H					
H250	250	120	18W-24W	Φ 245*H135	2.5kg	54*28*42cm/6pcs	15° / 30° / 45 ° / 60°
Q170	168	135	9W /7W	Φ 160*H145	1.25kg	53*36*47.8cm/18pcs	15° / 30° / 45 ° / 60°
Q150	150	110	5-9W	Φ 140*H20	1kg	50.5*50.5*26cm/18pcs	15° / 30° / 45 ° / 60°
Q130	130	110	5W /6W	Φ 125*H120	0.7kg	54.5*41*31cm/24pcs	15° / 30° / 45 ° / 60°
Q100A	100	108	3W	Φ 90*H120	0.45kg	56*34*25cm/30pcs	15° / 30° / 45 ° / 60°
Q100	100	75	3W	Φ 90*H85	0.42kg	53*32*22cm/30pcs	15° / 30° / 45 ° / 60°



K350




- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/R/G/B
- ◆ Material: Stainless steel cover+body, Tempered glass(Clear/Frosted), ABS box
- ◆ Input Voltage: 12V/24V

Technical Parameter

Model	Size(mm)		Rated Power	Hole Size(mm)	N.W(kg)	Packing Size	Angle (Lens)
	Φ	H					
K350	350	170	60W	Φ 340*H185	8.85kg	36*36*38cm/2pcs	15° / 30° / 45 ° / 60°
K250	250	120	18W-24W	Φ 245*H135	2.5kg	54*28*42cm/6pcs	15° / 30° / 45 ° / 60°
K210	210	135	18W-24W	Φ 196*H145	2.35kg	46*46*34.5cm/8pcs	15° / 30° / 45 ° / 60°
K190	190	125	15W	Φ 175*H135	1.9kg	41.5*41.5*48.5cm/12pcs	15° / 30° / 45 ° / 60°



240




- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/R/G/B
- ◆ Material: Stainless steel cover+body,Tempered glass(Clear/Frosted)
- ◆ Input Voltage: 12V/24V

Technical Parameter

Model	Size(mm)			Rated Power	N.W(kg)	Packing Size	Angle (Lens)
	Φ	ΦA	H				
240	240	100	220	24W	3.8kg	54*53*35cm/8pcs	15° /30° /45° /60°
210	210	200	220	18W	3.1kg	46*46*35cm/8pcs	15° /30° /45° /60°
190	190	100	200	12W	2.4kg	43*42*49cm/12pcs	15° /30° /45° /60°
145C	145	85	170	7W	1.1kg	53*37*49cm/18pcs	15° /30° /45° /60°



350



Technical Parameter

Model	Size(mm)			Rated Power	N.W(kg)	Angle (Lens)
	Φ	ΦA	H			
350	350	110	290	60W	11kg	15° /30° /45° /60°
270	270	200	180	36W	6.6kg	15° /30° /45° /60°






LED Pool/Underwater Recessed lights



G-85 (浇钢)




- ◆ Chip: Bridgelux
- ◆ CCT: 3000K/4000K/6000K/R/G/B
- ◆ Material: Cast steel cover+body, Tempered glass(Clear/Frosted)
- ◆ Input Voltage: 12V/24V

Technical Parameter

Model	Size(mm)			Rated Power	N.W(kg)	Packing Size	Angle (Lens)
	Φ	A	H				
G-85	85	120	75	3W	0.9kg	56*34*28cm/30pcs	15° /30° /45° /60°



J98 (浇钢)



Technical Parameter

Model	Size(mm)			Rated Power	N.W(kg)	Packing Size	Angle (Lens)
	Φ	ΦA	H				
J98	98	60	150	3W	1.35kg	38*35*34cm/24pcs	15° /30° /45° /60°
J140	140	70	190	5W/6W	2.75kg	52*35.5*26.5cm/12pcs	15° /30° /45° /60°
J170	170	70	200	12W	3.3kg	39*39*28.5cm/8pcs	15° /30° /45° /60°